

PRODUCT SOLUTIONS

DURATEC™ INTENSITY™



Duratec Intensity are a range of fun, bright solid colours that produce a big impact, delivered with warranty grade advanced super durable polyester thermosetting powder.



✓ **Super durable finish**

✓ **Excellent colour retention**

Suitable Substrates

Duratec Intensity is ideal for warranty grade applications over:

- Architectural aluminium including perforated and expanded aluminium.

Duratec Eternity can also be used on the following metals but these are not warranted:

- Steel (mild), bright/semi bright steel, black steel and blue steel.
- Galvanised steel, stainless steel, zincalume[®], non ferrous metals.

Warranted Benefits

The DGL Duratec Intensity range are supported by DGL Alumi Shield™ warranties when applied by a DGL Accredited Powder Coater to the warranty specification on recommended project types and conditions.

Alumi Shield™ Warranty

The Alumi Shield™ warranty is made up of two key components, a colour warranty (for fade and chalking) and a durability warranty (film integrity)



Terms and conditions apply

- The Alumi Shield™ colour Warranties are your assurance that Duratec Intensity will not:
 - Fade** – Fade testing will not give a delta E (Hunter) laboratory reading greater than five units from the original colour.
 - Chalk** – The rate of chalking will not exceed a rating of 2 for whites & pastels and a rating of 3 for deep colours as assessed in accordance with AS1580.481.1.11 test method.
- The Alumi Shield™ durability warranty covers the powder coating peeling, cracking or flaking during the warranty period, from the date the product is applied to the metal.
- Warranties are only valid when applied by a DGL Accredited Powder Coater to the warranty specification on recommended project types and conditions.

For more information visit dglpowders.com/warranties

Meets International Standards

With over 50 years of experience, the AAMA (American Architectural Manufacturer's Association) is regarded as the standards leader for finishes on architectural aluminium. DGL Duratec Intensity is formulated to meet: AAMA 2603 and AAMA 2604 as well as Australian standard AS 3715.

For more information visit aamanet.org

Project Suitability

Project Types

Duratec Intensity is ideal for most interior and exterior project types (incl. all BCA classes) on steel and aluminium.

	NON-HABITABLE	RESIDENTIAL <4 LEVELS	RESIDENTIAL >3 LEVELS	COMMERCIAL <4 LEVELS	COMMERCIAL >3 LEVELS	PRESTIGIOUS COMMERCIAL	MONUMENTAL
INTERIOR	●	●	●	●	●	●	●
EXTERIOR	●	●	●	●	●	●	

- Non-Habitable projects are those that are not dwelling types. Examples can be furniture, bus shelters, signage etc.
- Residential properties are typically easy to maintain, given their height and access.
- High-rise projects are less sheltered from neighbouring buildings, raising their exposure and reducing their ease of maintenance.
- Monumental projects attract the most attention and have the highest standards required to uphold the reputation expected from landmark sites.

Project Suitability - Aluminium

Project Type	Environment	Conditions	Duratec Intensity
Monumental	Exterior	Mild, Severe or Tropical	
Prestigious Commercial	Exterior	Mild, Severe or Tropical	●
Commercial	Exterior	Mild, Severe or Tropical	●
Residential	Exterior	Mild, Severe or Tropical	●
Non-Habitable	Exterior	Mild, Severe or Tropical	●
All Projects	Interior	Moderate Interior	●
All projects	Interior	General Interior	●

● Alumi Shield™ warranty available

Duratec Intensity is only suitable for coastal environments > 10m from the high tide and is NOT suitable in strongly acidic or caustic environments so pH must be between 5 and 9.

Please refer to Interior and exterior environments close to liquids for warranty implications where powder coatings may be in close proximity to liquids other than the sea.

Alumi Shield™ Warranties on perforated and expanded aluminium are available for Duratec Intensity in the following environments:

- Interior: General Interior conditions (E-Prime base coat not mandatory); Moderate Interior (E-Prime base coat mandatory).
- Exterior: Mild (E-Prime base coat not mandatory); Severe and tropical: (E-Prime basecoat mandatory).

For more information about specifications on perforated and expanded aluminium visit dglpowders.com

Conditions

Use the following table which references AS2312.1 and AS3715 to identify the environment, conditions and atmospheric corrosivity categories.

Environment	Conditions	Corrosivity level & Zone	Former AS/NZ 2312 Category	Mild Steel Corrosion Rate ¹	Example environments
Exterior Environment:	Mild	Low (C2) Medium (C3)	B C	1.3 - 25 25-50	Arid, urban, inland city Industrial, geothermal ² and coastal
	Severe	High (C4), Very high (C5-M, C5-I)	D E-M, E-I	50-80 80-200	Sea shore (calm) Sea shore (surf), offshore Islands ³ & or heavy industrial
	*Tropical	Very high (T)	F	80-200	High, humid and monsoonal locations and islands ⁴
Interior Environments	General Interior	Very low(C1) Low (C2)	A B	<1.3 1.3-25	Dry interiors (offices, shops) Minor condensation (warehouses, sports halls)
		Medium (C3) High (C4)	C D	25-50 50-80	High moisture (food processing plants, breweries, dairies) Significant contamination (swimmings pools)

*Tropical projects - It is recommended to speak to a DGL Account Manager or call the advice line for all projects in Tropical locations.

1. Corrosion rate is for uncoated steel ref AS2312.1.

3. Offshore islands that are not tropical include Waiheke, Stewart Island, Fraser Island etc.

2. Geothermal environments with a PH>5 and <9. For PH outside this consult DGL.

4. Tropical islands include Australian Islands north of Mackay and Pacific islands such as PNG, Fiji, Samoa, Tonga.

Project Suitability - Steel

Use the following table to help identify where Duratec Intensity can be applied on steel projects and the recommended system required. Refer to the conditions information to determine the environment that your project will be exposed to.

Corrosion Category			Primer System		Top Coat
Project Type	Environment	Conditions (incl Corrosivity Level)	Zincshield	E-Prime™	Duratec Intensity
Prestigious Commercial	Exterior	Severe or Tropical (High to very high)	✓	✓	●
Prestigious Commercial	Exterior	Mild (Medium)	✓ ¹	✓ ²	●
Prestigious Commercial	Exterior	Mild (Low)	✓		●
Commercial Developments	Exterior	Severe or Tropical (High to very high)	✓	✓	●
Commercial Developments	Exterior	Mild (Medium)	✓ ¹	✓ ²	●
Commercial Developments	Exterior	Mild (Low)	✓		●
Residential	Exterior	Severe or Tropical (High to very high)	✓	✓	●
Residential	Exterior	Mild (Medium)	✓ ¹	✓ ²	●
Residential	Exterior	Mild (Low)	✓		●
Non Habitable	Exterior	Severe or Tropical (High to very high)	✓	✓	●
Non Habitable	Exterior	Mild (Medium)	✓ ¹	✓ ²	●
Non Habitable	Exterior	Mild (Low)	✓		●
All Projects	Interior	Moderate Interior (High)	✓	✓	●
All Projects	Interior	Moderate Interior (Medium)	✓ ¹	✓ ²	●
All Projects	Interior	General Interior (Very low to low)	✓		●

Duratec Intensity is only suitable for coastal environments >10m from the high tide and is NOT suitable in strongly acidic or caustic environments so pH must be between 5 and 9. Please refer to Interior and exterior environments close to liquids for warranty implications where powder coatings may be in close proximity to liquids other than the sea.

1. In Mild (Medium) exterior and Moderate Interior (medium) environments a Zincshield and Duratec Intensity system can be used.
2. In Mild (Medium) exterior and Moderate Interior (medium) environments a Zincshield, E-Prime and Duratec Intensity system is highly recommended.

It is recommended to speak to a DGL Account Manager for all C5 projects.

Interior and exterior environments close to liquids other than the sea

For powder coated assets close to liquids other than the sea, e.g. fences near swimming pools, fountains, bathrooms or furniture etc, please refer to the guidance below to understand the warranty limitations in these environments.

	1Chemically Treated	Clean Tap, Fresh or Potable Water	Salt Water	Other
Duratec Intensity	■	●	■	Seek advice from DGL

1. Please note chemically treated water includes antimicrobial treatments, e.g. in pools, anti-corrosive chemicals, and soapy water in bathrooms and showers.

■ Where indicated Alumi Shield™ warranties are available on areas >than 2m from the liquid (ie outside the splash zone).

● Where indicated Alumi Shield™ and Steel Shield™ warranties are available any distance from the liquid.

All DGL powder products are NOT suitable in strongly acidic or caustic environments so pH must be between 5 and 9.

Alumi Shield™ warranties are not available if the powder coating is immersed in any liquid.

Care and Maintenance

To ensure the life of your asset is maximised and to comply with DGL warranty requirements, **a simple and regular maintenance program must be implemented** and recorded in line with the DGL Powders Care and Maintenance brochure.

For more information refer to the DGL Powders Care and Maintenance brochure available at dglpowders.com.au/tech-advice

Product Summary

Product Features

Product Features	
Warranties	Alumi Shield™ available - refer to Warranty Benefits.
Technology	Super durable polyester thermosetting powder.
Look	Bright solid.
Finish	Satin and Gloss.
Colour range	Available in a range of 9 core colours. View the range in DGL Colour Selectors, on Aluminium Swatches, or online. Cards and swatches can be ordered from dglpowders.com . If you cannot find the colour you require DGL can offer a Custom Colour Service. For more information visit dglpowders.com
Standards met	Formulated to meet: AS 3715, AAMA 2603 and AAMA 2604.
Product Benefits	
Colour retention	Excellent colour retention.
Durability	Super durable finish.
Look	Long lasting bright, solid finish.

Securing your Warranty

Request a Specification

Our dedicated and knowledgeable specification consultants can help simplify the specification process, saving you time and money by ensuring you achieve the best coating specification for the job. They can provide:

- Documented project specific specifications.
- Written confirmation of your project's eligibility for an Alumi Shield™ warranty.
- Design, coating system and colour advice.
- Color samples

For information visit dglpowders.com

DGL Accredited Powder Coaters

Only DGL Accredited Powder Coaters are able to issue our DGL Alumi Shield™ warranties after demonstrating their capability to meet stringent quality conditions and international standards. Every project they complete is audited and samples are tested at our Australian and New Zealand technical centres to ensure they meet the strict standards required to gain a DGL warranty.



认可粉末喷涂厂

For information visit dglpowders.com/accredited



The project: Mac Addict
Location: QV, Melbourne

Photo credit: Eve Wilson and Larritt-Evans

Advice Line

Our dedicated consultants can help simplify the specification process, saving you time and money by providing the right coating advice for your project. Visit dglpowders.com/contact-us

Offices

Australia

DGL International Powder Coatings
1-15 Pound Road West
Dandenong South VIC 3175
☎ (61) 3 8787 4500

New Zealand

DGL International Powder Coatings
31B Hillside Road
Glenfield, Auckland, New Zealand
☎ (64) 9 441 8244

Singapore

DGL International Powder Coatings
No.100 Pasir Panjang Road
#02-10, Singapore 118518
☎(65) 6 838 1010

China

DGL International Powder Coatings
Room 406, No.8, Lane 1977, JinShaJiang Road,
Shanghai, China, PC 200333
☎ (86) 21 6173 8800